

# ferrodynamics recording tape

**SPLICE FREE**

## NEW IMPROVED EXCLUSIVE DRY SYNTHETIC LUBRICANT

- ★ No squeal, no gumming of heads, vastly reduced head wear

## NEW HARDER SCRATCH-RESISTANT FORMULATION

- ★ No flake-off, peeling or deposit on guides and heads

## INCREASED OUTPUT

- ★ Reduced distortion at same recording level

## IMPROVED FREQUENCY RESPONSE

- ★ Sharper, brighter recordings

## IMPROVED UNIFORMITY

- ★ Lower modulation noise

## NEW STURDY ONE-PIECE QUICK THREADING REEL OF MS-19X

- ★ Stable, warp-free operation

TAPE NO.	JOB NO.	DATE	ORIGIN	MACHINE	SPEED	ENGINEER
PROGRAM					EDITED	
CUSTOMER					ERASE AFTER	
REMARKS						

- MONAURAL   
  STEREO   
  FULL TRACK   
  HALF TRACK   
  ¼ TRACK

DESCRIPTION

**WARRANTY:** Ferrodynamics Magnetic Recording Tape is manufactured by a pioneer in the industry utilizing the most modern precision equipment. Strict quality control of the materials and processes is exercised by engineering personnel to assure consistent high quality.

Buyers shall determine that contents are the proper kind for intended use. If defective in packaging, labeling or manufacture, contents will be replaced. There are no other warranties expressed or implied.

### RECORDING TIME PER TRACK

	1½ ips	3¾ ips	7½ ips	15 ips
150'	15 min	7½ min	3¾ min	1¾ min
300'	30 min	15 min	7½ min	3¾ min
600'	1 hr	30 min	15 min	7½ min
900'	1 hr 30 min	45 min	22½ min	11½ min
1200'	2 hrs	1 hr	30 min	15 min
1800'	3 hrs	1 hr 30 min	45 min	22½ min
2400'	4 hrs	2 hrs	1 hr	30 min

A Product of the Ferrodynamics Corp., Lodi, N. J.

Made in U.S.A.